



INDUCORD®

Industriewaterslang.

Geschikt voor water, gier, lichte zuren en logen.

Temperatuurbereik: -30°C tot +70°C
Binnenwand: SBR, zwart, glad
Buitenwand: SBR, zwart, met doekafdruk

Opdruk: **INDUCORD® WATER / WASSER PN 10 BAR (INW. 254 MM 6 BAR)**

I.D. mm	U.D. mm	W.D. bar	B.D. bar	Lengte m
22	30	10	30	40
25	35	10	30	40
28	38	10	30	40
32	43	10	30	40
35	46	10	30	40
38	50	10	30	40
40	52	10	30	40
42	54	10	30	40
45	57	10	30	40
48	60	10	30	40
51	64	10	30	40
60	73	10	30	40
63,5	77,5	10	30	40
70	84	10	30	40
76	90	10	30	40
80	94	10	30	40



GAASBEEK B.V.

slangen - koppelingen - kompensatoren

I.D. mm	U.D. mm	W.D. bar	B.D. bar	Lengte m
90	104	10	30	40
102	116	10	30	40
110	126	10	30	20
127	144	10	30	20
152	170	10	30	20
203	224	10	30	20
254	275	6	18	10



's-Gravelandseweg 369 - 3125 BJ Schiedam - The Netherlands
Tel. +31 (0)10 462 39 11 - Fax +31 (0)10 462 55 04 - E-mail info@thmgaasbeek.nl - www.thmgaasbeek.nl
Rabobank rek.nr. 36.19.09.640 - IBAN NL45RABO0361909640 - BTW nr. NL 800480065B01

Alle leveringen geschieden volgens onze leveringsvoorwaarden gedeponoord bij de K.v.K. te Rotterdam onder nr. 24248378

