



RADIACORD®

Koelwaterslang.

Bestand tegen de gebruikelijke antivries middelen.

Temperatuurbereik: -30°C tot +100°C
Binnenwand: EPDM, zwart, glad
Buitenwand: EPDM, zwart, met doekafdruk
*Buitenwand EPDM, zwart, glad,
Geëxtrudeerd.

Opdruk: RADIACORD® PN .. BAR MAX. 100° C

I.D. mm	U.D. mm	W.D. bar	Lengte m
10	17	6	40
13	20	6	40
15	22	6	40
18	25	6	40
20	27	6	40
22	29	6	40
25	32	6	40
28	35	4	40
30	37	4	40
32	39	4	40
35	42	4	40
38	45	4	40
40	47	4	40
42	49	4	40
45	53	4	40
48	56	4	40



GAASBEEK B.V.

slangen - koppelingen - kompensatoren

I.D. mm	U.D. mm	W.D. bar	Lengte m
50	59	4	40
60	70	4	40
63	73	4	40
76	84	4	40
90	98	4	20
102	110	4	40
110	122	4	20



's-Gravelandseweg 369 - 3125 BJ Schiedam - The Netherlands
Tel. +31 (0)10 462 39 11 - Fax +31 (0)10 462 55 04 - E-mail info@thmgaasbeek.nl - www.thmgaasbeek.nl
Rabobank rek.nr. 36.19.09.640 - IBAN NL45RABO0361909640 - BTW nr. NL 800480065B01

Alle leveringen geschieden volgens onze leveringsvoorwaarden gedeponereerd bij de K.v.K. te Rotterdam onder nr. 24248378

